

LOADER PLUS - Especificaciones técnicas



Description

LOADER PLUS (L-3) es un neumático con estructura diagonal, particularmente proyectado para cargadoras. La mezcla de la banda de rodadura ofrece características de resistencia a cualquier tipo de corte y es ideal para operaciones de carga o nivelación.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Buldócer • Pala cargadora

OTR: Buldócer • Pala cargadora

Version	STANDARD
Type	TT
Tyre Size	14.00 - 25

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	375
Overall Diameter (mm)	1368
Static Loaded Radius (mm)	630
Rolling Circumference (mm)	4050
Rim Rec	10.00/1.5
TRA Code	L3

Load capacity (Kg)

km/h / bar	7.00
10	8500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 17:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..