

## LOADER SPECIAL - Especificaciones técnicas



### Description

LOADER SPECIAL (L-5) es un neumático con estructura diagonal que mantiene las cargadoras en movimiento, asegurando una excelente eficiencia en las operaciones pesadas con rocas. Su óptima tracción y excepcional resistencia a los cortes darán un impulso a la productividad.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Buldócer • Pala cargadora

Version	STEEL BELTED
Type	TL
Tyre Size	40/65 - 39

## Dimensions International Standard

Ply Rating	56
Overall Width (mm)	1000
Overall Diameter (mm)	2405
Rim Rec	32.00/4.0
TRA Code	L5

## Load capacity (Kg)

	km/h / bar	7.25
	10	38750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 8:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..