

MAGLIFT SMOOTH - Especificaciones técnicas



Description

MAGLIFT SMOOTH ha sido especialmente desarrollado para equipos de apoyo en tierra (GSE), remolques portuarios e industriales que operan en superficies lisas. El neumático está fabricado con una mezcla especial en la banda de rodadura que garantiza una excelente resistencia a todo tipo de cortes y una larga vida útil. El diseño liso de la banda de rodadura y su máxima superficie de contacto ofrecen una extraordinaria estabilidad y una distribución optimizada de la carga, incluso en condiciones de servicio extremas. MAGLIFT SMOOTH es sinónimo de excelente tracción, baja resistencia a la rodadura y baja emisión de calor, garantizando una mayor eficiencia. Además, el borde de protección de la llanta especialmente diseñado protege el neumático contra posibles daños, mientras que la estructura reforzada del talón garantiza un excepcional agarre y elimina cualquier riesgo de deslizamiento durante el funcionamiento.

UM

International Standard

Construction

◆ SOLID

Machinery

Industrial: Remolque

Version	STANDARD
Type	
Tyre Size	11.00 - 20

Dimensions International Standard

Section Width (mm)	256
Overall Diameter (mm)	1055
Rim Rec	8.00 - 20

Load capacity (Kg)

km/h / bar	-
25 LOAD WHEEL	6540
25 STEER WHEEL	5450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..