

MH TR 182 - Especificaciones técnicas



Description

MH TR 182 es idóneo para los vehículos que transportan casas móviles. Este neumático de alta velocidad que se utiliza principalmente por carretera, ofrece significativos ahorros de carburante. MH TR 182 asegura una larga duración y elevadas prestaciones durante todo el ciclo de vida del producto.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Casa móvil

Version	STANDARD
Type	TL
Tyre Size	8 - 14.5

Dimensions International Standard

Ply Rating	8
Section Width (mm)	207
Overall Diameter (mm)	710
Rim Rec	6.00 MH

Load capacity (Kg)

km/h / bar	4.80
100	1030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 5:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..