

MINE STAR XL - Especificaciones técnicas



Description

MINE STAR XL es un neumático de estructura diagonal especialmente idóneo para cargadoras LHD en las operaciones subterráneas de carga y de transporte. El diseño ancho de la banda de rodadura con los tacos abiertos evita la retención de piedras y proporciona una tracción excepcional. La huella más ancha hace de MINE STAR XL su mejor aliado para operaciones de minería subterránea de servicio pesado. MINE STAR XL ha sido realizado con una mezcla especial de la banda de rodadura que proporciona una extraordinaria resistencia a los cortes y los desgarros, asegurando una mayor eficiencia operativa, así como un ciclo de vida prolongado del neumático con menores tiempos de parada de la máquina.

UM

International Standard

Construction

BIAS

Machinery

OTR: Cargadora LHD

Version	STANDARD
Type	TL
Tyre Size	55 X 20.00 - 34

Dimensions International Standard

Ply Rating	44
Section Width (mm)	485
Overall Diameter (mm)	1365
Rim Rec	16.00
TRA Code	L5
Tread Depth	61

Load capacity (Kg)

km/h / bar	10.00
5	18755
10	16600
15	15435
25	14115

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/04/2025 20:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..