

MP 567 - Especificaciones técnicas



Description

MP 567 es un neumático agro-industrial idóneo para desplazarse tanto por el campo como por la carretera, así como utilizarlo en los trabajos realizados en el sector de la municipalidad/mantenimiento. Es el neumático ideal para maquinaria agrícola y elevadores telescópicos. MP 567 ofrece una óptima tracción en todas las condiciones atmosféricas, así como excelentes propiedades de auto-limpieza. Este neumático asegura una experiencia de conducción confortable y un ciclo de vida más largo.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricultura: Maquinaria agrícola • Elevador telescópico
Industrial: Elevador telescópico • Vehículo universal

Version	STANDARD
Type	TL
Tyre Size	10.5 - 20

Dimensions US Standard

Usa code	94038091
Ply Rating	10
Section Width (inch)	10.6
Overall Diameter (inch)	37.6
Static Loaded Radius (inch)	17.5
Rolling Circumference (inch)	113.4
Rim Rec	9
Rim Alt	9 SDC
ECE	E4-54R-0022630

Load capacity (lbs)

	mph / psi	54
	55	3970
	25	4560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 23:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..