

## MP 567 - Especificaciones técnicas



### Description

MP 567 es un neumático agro-industrial idóneo para desplazarse tanto por el campo como por la carretera, así como utilizarlo en los trabajos realizados en el sector de la municipalidad/mantenimiento. Es el neumático ideal par maquinaria agrícola y elevadores telescópicos. MP 567 ofrece una óptima tracción en todas las condiciones atmosféricas, así como excelentes propiedades de auto-limpieza. Este neumático asegura una experiencia de conducción confortable y un ciclo de vida más largo.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Maquinaria agrícola • Elevador telescópico  
Industrial: Elevador telescópico • Vehículo universal

Version	IMPLEMENT
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS DRIVE WHEEL	130 A8
LI/SS FREE ROLLING	143 A8

## Dimensions US Standard

Usa code	94057603
Ply Rating	18
TMPH	1
Section Width (inch)	11.5
Overall Diameter (inch)	34.2
Static Loaded Radius (inch)	15.5
Rolling Circumference (inch)	101.5
Rim Rec	9.0
ECE	E11-106R-003392

## Load capacity (lbs)

mph / psi	87
25 FR	6010
25 DW	4190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 4:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..