

MP 567 - Especificaciones técnicas



Description

MP 567 es un neumático agro-industrial idóneo para desplazarse tanto por el campo como por la carretera, así como utilizarlo en los trabajos realizados en el sector de la municipalidad/mantenimiento. Es el neumático ideal par maquinaria agrícola y elevadores telescópicos. MP 567 ofrece una óptima tracción en todas las condiciones atmosféricas, así como excelentes propiedades de auto-limpieza. Este neumático asegura una experiencia de conducción confortable y un ciclo de vida más largo.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Elevador telescópico
Industrial: Elevador telescópico • Vehículo universal

Version	IMPLEMENT
Type	TL
Tyre Size	11.5/80 - 15
LI/SS DRIVE WHEEL	123 A8
LI/SS FREE ROLLING	135 A8

Dimensions US Standard

Usa code	94054930
Ply Rating	12
Section Width (inch)	11.4
Overall Diameter (inch)	34.4
Rim Rec	8 LB
ECE	E11-106R-004621

Load capacity (lbs)

mph / psi	60
25 FR	4800
25 DW	3420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 1:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..