

## MP 570 - Especificaciones técnicas



### Description

MP 570 es un neumático agro-industrial idóneo para las excavadoras y las ternas. Este neumático asegura optimas tracción y durabilidad, así como excelentes características de auto-limpieza en todas las condiciones operativas.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Cargadora retroexcavadora

Industrial: Cargadora retroexcavadora • Pala excavadora •

Vehículo universal

Version	STANDARD
Type	TL
Tyre Size	14.5 - 20

## Dimensions US Standard

Usa code	94015252
Ply Rating	12
Section Width (inch)	14.2
Overall Diameter (inch)	43.9
Static Loaded Radius (inch)	19.9
Rolling Circumference (inch)	130.9
Rim Rec	11
Rim Alt	12 SDC
ECE	E11-106R-005342

## Load capacity (lbs)

	mph / psi	44
	40	5360
	30	5510

Printed on 02/07/2024 19:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..