

MP 590 - Ficha técnica



Description

MP 590 es un neumático agro-industrial que se utiliza en las operaciones de carga con elevadores telescópicos y carretillas elevadoras. Este neumático ofrece una óptima tracción y una excelente estabilidad, así como una durabilidad incrementada.

UM

US Standard

Construction

BIAS

Machinery

Agricultura: Elevador telescópico

Industrial: Carretilla elevadora • Elevador telescópico •

Vehículo universal

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 - 22.5 (445/65 - 22.5)	STANDARD	94044191	20	14.0		18.9	46.9	20.9	139.1	TL	E11-106R-004408
18 - 22.5 (445/65 - 22.5)	STANDARD	94014729	16	14.0		18.9	46.9	20.9	139.1	TL	E11-106R-003019

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..