

MP 600 - Especificaciones técnicas



Description

MP 600 es un neumático agro-industrial idóneo para las operaciones de carga con elevadores telescópicos y maquinaria agrícola. Este neumático ofrece una óptima tracción y una excelente estabilidad, así como un prolongado ciclo de vida del producto.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Elevador telescópico
Industrial: Elevador telescópico • Vehículo universal

Version	STANDARD
Type	TL
Tyre Size	10.5 - 18

Dimensions US Standard

Usa code	94015290
Ply Rating	10
Section Width (inch)	10.7
Overall Diameter (inch)	36.2
Static Loaded Radius (inch)	16.5
Rolling Circumference (inch)	107.9
Rim Rec	9
Rim Alt	9 SDC
ECE	E11-106R-003581

Load capacity (lbs)

	mph / psi	54
	25 DW	4300
	30 DW	4190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 12:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..