

MP 600 - Ficha técnica



Description

MP 600 es un neumático agro-industrial idóneo para las operaciones de carga con elevadores telescópicos y maquinaria agrícola. Este neumático ofrece una óptima tracción y una excelente estabilidad, así como un prolongado ciclo de vida del producto.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Elevador telescópico
Industrial: Elevador telescópico • Vehículo universal

SIZE	Version	LI/SS DRIVE WHEEL	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.5 - 18	STANDARD		10	9	9 SDC	272	920	420	2740	TL	E11-106R-003581
12.5 - 18	STANDARD		10	11	12 SDC	308	990	450	2950	TL	
12.5 - 18	STANDARD		12	11	12 SDC	308	990	450	2950	TL	
400/70 - 20 (16.0/70 - 20)	STANDARD		14	13 SDC	12	405	1085	0	0	TL	
400/70 - 24 (16.0/70 - 24)	SPECIAL		14	13 SDC	12	405	1185	545	3530	TL	
400/70 - 24 (16.0/70 - 24)	STANDARD		14	13 SDC	12	405	1185	545	3530	TL	E11-106R-003640
400/70 - 24 (16.0/70 - 24)	STANDARD		10	13 SDC	12	405	1185	545	3530	TL	
400/70 - 24 (16.0/70 - 24)	STANDARD	158 A8	18	13 SDC	12	405	1185	545	3530	TL	E11-106R-003641

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 12:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..