

MP 600 - Ficha técnica



Description

MP 600 es un neumático agro-industrial idóneo para las operaciones de carga con elevadores telescópicos y maquinaria agrícola. Este neumático ofrece una óptima tracción y una excelente estabilidad, así como un prolongado ciclo de vida del producto.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Elevador telescópico
Industrial: Elevador telescópico • Vehículo universal

SIZE	Version	USACode	LI/SS DRIVE WHEEL	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.5 - 18	STANDARD	94015290		10	9	9 SDC	10.7	36.2	16.5	107.9	TL	E11-106R-003581
12.5 - 18	STANDARD	94015306		10	11	12 SDC	12.1	39	17.7	116.1	TL	
12.5 - 18	STANDARD	94015313		12	11	12 SDC	12.1	39	17.7	116.1	TL	
400/70 - 20 (16.0/70 - 20)	STANDARD	94048403		14	13 SDC	12	15.9	42.7	0	0	TL	
400/70 - 24 (16.0/70 - 24)	SPECIAL	94051618		14	13 SDC	12	15.9	46.7	21.5	139	TL	
400/70 - 24 (16.0/70 - 24)	STANDARD	94015320		14	13 SDC	12	15.9	46.7	21.5	139	TL	E11-106R-003640
400/70 - 24 (16.0/70 - 24)	STANDARD	94042043		10	13 SDC	12	15.9	46.7	21.5	139	TL	
400/70 - 24 (16.0/70 - 24)	STANDARD	94049318	158 A8	18	13 SDC	12	15.9	46.7	21.5	139	TL	E11-106R-003641

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 12:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..