

MT 617 - Ficha técnica



Description

MT 617 ha sido específicamente desarrollado para camiones militares. Es un neumático **run-flat** (autoportante) que ofrece una óptima tracción, así como una elevada resistencia a las perforaciones. Además, la protección del flanco contribuye a que este neumático tenga un ciclo de vida más prolongado.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Camión militar

| SIZE | Version | USACode | PR | RIM REC | RIM ALT | SW | OD | Type |
|-----------|---------------|----------|----|---------|---------|------|----|------|
| 14.5 - 21 | ARAMID BELTED | 94030880 | 12 | 10 | | 15.4 | 48 | TL |
| 14.5 - 21 | STANDARD | 94030750 | 12 | 10 | | 15.4 | 48 | TL |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 0:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..