

MULTIMAX MP 529 - Ficha técnica



Description

El MULTIMAX MP 529 es un neumático radial polivalente con cinturones de acero diseñado para elevadores telescopicos utilizados en aplicaciones industriales. El diseño de la banda de rodadura se ha desarrollado específicamente para superficies duras. El robusto flanco del neumático y una huella más ancha garantizan una estabilidad extraordinaria en modalidad de levantamiento. El MULTIMAX MP 529 se distingue, además, por su sólida carcasa, resistente a las perforaciones, y está realizado con un compuesto especialmente resistente a los cortes y los desgarres, lo que se traduce en una elevada durabilidad y una larga vida operativa del neumático.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Elevador telescopico

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
340/80 R 18	STANDARD	94054305	143 A8/B	11 ; 11 SDC ; W 11	W 10 ; 12 ; 12 SDC	13.5	39.4	17.5	118.4	TL	E11-106R-002972

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..