

MULTIMAX MP 540 - Especificaciones técnicas



Description

BKT ha diseñado MULTIMAX MP 540 para todos los vehículos multiuso. Gracias a la carcasa All Steel, MULTIMAX MP 540 permite llevar cargas pesadas dentro y fuera de la carretera. Además, su diseño de patrón de bloques ofrece una estabilidad y una durabilidad excepcionales.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Vehículo universal

Industrial: Vehículo universal

Version	STANDARD
Type	TL
Tyre Size	405/70 R 24 (16.0/70 R 24)
LI/SS	152 J

Dimensions US Standard

Usa code	94074600
Overall Width (inch)	15.8
Overall Diameter (inch)	46.2
Static Loaded Radius (inch)	20.9
Rolling Circumference (inch)	141.2
Rim Rec	13
ECE	E11-54R-0020862

Load capacity (lbs)

mph / psi	73
62	7830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..