

MULTIMAX SR 261 - Especificaciones técnicas



Description

MULTIMAX SR 261 es un neumático radial All Steel con cinturones de acero multicapa especialmente diseñado para remolques de plataforma baja, remolques agrícolas y grúas portuarias móviles en aplicaciones de transporte y operaciones portuarias.

Su fuerte carcasa y el compuesto especial de la banda de rodadura garantizan una mayor vida útil del neumático. Gracias a su diseño de banda de rodadura con laminillas, MULTIMAX SR 261 ofrece una tracción superior en todas las aplicaciones.

Además, el exclusivo diseño de la banda de rodadura de 5 rebordes maximiza el contacto con el suelo para un desgaste uniforme de la banda de rodadura.

UM

US Standard

Construction

 RADIAL

Machinery

Industrial: Remolque da plataforma baja • Grúa móvil

Version	STANDARD
Type	TL
Tyre Size	285/70 R 19.5
LI/SS	150/148 J

Dimensions US Standard

Usa code	94067688
Overall Width (inch)	11
Overall Diameter (inch)	35.6
Static Loaded Radius (inch)	16.2
Rolling Circumference (inch)	109.4
Rim Rec	8.25
Rim Alt	7.50 ; 9.00

Load capacity (lbs)

mph / psi	130
62 Load Single	7400
62 Load Dual	6950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 0:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..