

## PAC MASTER - Especificaciones técnicas



### Description

PAC MASTER es un neumático diagonal que se utiliza en las máquinas compactadoras. Proporciona una elevada estabilidad y asegura un ciclo de vida prolongado. Este neumático está realizado con una mezcla especial que proporciona una particular resistencia al calor.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Compactador

Version	STANDARD
Type	TL
Tyre Size	10.5/80 - 16

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	275
Overall Diameter (mm)	810
Static Loaded Radius (mm)	382
Rolling Circumference (mm)	2480
Rim Rec	8.0
ECE	E11-106R-005274

## Load capacity (Kg)

km/h / bar	4.50
10	1850
15	1500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 13:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..