

## PAC MASTER - Especificaciones técnicas



### Description

PAC MASTER es un neumático diagonal que se utiliza en las máquinas compactadoras. Proporciona una elevada estabilidad y asegura un ciclo de vida prolongado. Este neumático está realizado con una mezcla especial que proporciona una particular resistencia al calor.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Compactador

Version	STANDARD
Type	TT
Tyre Size	9.5/65 - 15

## Dimensions US Standard

Usa code	94036141
Ply Rating	6
Section Width (inch)	9.3
Overall Diameter (inch)	26.6
Rim Rec	7.0
ECE	E11-106R-005303

## Load capacity (lbs)

mph / psi	47
5	2910
10	2340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 13:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..