

PL 801 - Especificaciones técnicas



Description

PL 801 ha sido particularmente desarrollado para los rastrillos hileradores rotativos y los volteadores de heno, así como para las operaciones de logística realizadas con carretillas elevadoras. Este neumático ofrece una excelente estabilidad, así como una elevada resistencia a cualquier tipo de corte. PL 801 asegura un ciclo de vida prolongado del neumático.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Cosechadora • Rastrillo hilerador rotativo •
Carretilla elevadora
Industrial: Carretilla elevadora

Version	STANDARD
Type	TT
Tyre Size	7.00 - 12

Dimensions International Standard

Ply Rating	14
Section Width (mm)	189
Overall Diameter (mm)	692
Rim Rec	5.00 S
ECE	E11-106R-003398

Load capacity (Kg)

	km/h / bar	9.00
25 LOAD WHEEL		2755
25 STEER WHEEL		2120
10 OTHER VEHICLES		2755
25 OTHER VEHICLES		2120
STATIC SIDE LOADER		3200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 13:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..