

POWER TRAX HD (FL) - Especificaciones técnicas



Description

El POWER TRAX HD es un neumático de elevada calidad realizado con telas cruzadas y ha sido específicamente diseñado para las carretillas elevadoras que se utilizan en el sector industrial. Su profunda banda de rodadura y el flanco con un espesor extra, así como su robusta carcasa, se traducen en una extraordinaria durabilidad, minimizando el riesgo de perforación y de daños accidentales. Este neumático se caracteriza por la excelente resistencia a los cortes, los desgarres y las laceraciones, que hace que sea idóneo para las superficies cementadas, rugosas y duras. El borde de protección de la llanta, especialmente diseñado, protege el neumático en el área de la pestaña de la llanta contra desinflamientos y daños.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Carretilla elevadora

Version	STANDARD
Type	TT
Tyre Size	5.00 - 8

Dimensions US Standard

Usa code	94007790
Ply Rating	10
Section Width (inch)	5.7
Overall Diameter (inch)	18.9
Rim Rec	3.00 D
Rim Alt	3.25 I

Load capacity (lbs)

	mph / psi	145
15 LOAD WHEEL		3120
15 STEER WHEEL		2405
5 OTHER VEHICLES		3120
15 OTHER VEHICLES		2405
STATIC SIDE LOADER		3625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..