

POWER TRAX - Ficha técnica



Description

POWER TRAX es un neumático de primera calidad especialmente diseñado para el servicio pesado en remolques portuarios, manipuladores de contenedores vacíos o ECH y maquinarias de minería subterránea. Su profunda banda de rodadura y su resistente carcasa proporcionan una durabilidad excepcional, por lo que disminuye el riesgo de pinchazos y daños accidentales. POWER TRAX es el neumático ideal para operaciones duras y resistentes, gracias al exclusivo compuesto de la banda de rodadura, que proporciona una excelente resistencia a cortes y desperfectos.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Manipulador de contenedores vacíos
OTR: Vehículos para minería subterránea

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
355/65 - 15	STANDARD	170 A5	24	9.75		335	830	380	2530	TL
12.00 - 20	STANDARD	176 A5	20	8.5	9.0	320	1150			TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 0:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..