

RIB 324 - Ficha técnica



Description

RIB 324 ha sido desarrollado con un dibujo de bloques en la banda de rodadura y un amplia área de contacto asegurando óptima estabilidad en suelos sueltos y terrenos arenosos. La carcasa de nylon y el flanco robustos, así como la mezcla especial de la banda de rodadura se traducen en una resistencia elevada a la perforación y al desgaste, así como una mayor capacidad de carga.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola

Industrial: Remolque

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type
66 X 44.00 - 25	STANDARD	94064274	20	36.0 TH		43.7	66.9	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..