

RIB 774 (B) - Especificaciones técnicas



Description

RIB 774 (B) es un neumático de sección baja para maquinaria agrícola, ideal para la agricultura moderna. Este neumático es idóneo para aplicaciones por carretera y fuera de carretera con maquinaria agrícola y remolques. Este neumático asegura una capacidad elevada de carga y un amplio ciclo de vida del producto. Hay disponible una versión "HD" para las operaciones más pesadas.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Remolque
Industrial: Remolque

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	141 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	391
Overall Diameter (mm)	850
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2490
Rim Rec	13.00
Rim Alt	13
ECE	E11-106R-004311

Load capacity (Kg)

	km/h / bar	3.70
	10 FR	3605
	25 FR	3065
	30 FR	2885
	40 FR	2575

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 19:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..