

RIB 774 (C) - Especificaciones técnicas



Description

RIB 774 (C) es un neumático de sección baja con base estrecha (narrow) para maquinaria agrícola. Este neumático es ideal para aplicaciones de recogida de heno y de transporte con empacadoras de heno y remolques por carretera y fuera de carretera. Este neumático asegura una capacidad elevada de carga y un amplio ciclo de vida del producto.

UM

International Standard

Construction

BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora • Remolque

Version	STANDARD
Type	TL
Tyre Size	225/75 - 17.5
LI/SS FREE ROLLING	139 A8

Dimensions International Standard

Ply Rating	16
Section Width (mm)	220
Overall Diameter (mm)	775
Static Loaded Radius (mm)	360
Rolling Circumference (mm)	2310
Rim Rec	6.75
ECE	E11-106R-004591

Load capacity (Kg)

km/h / bar	9.00
10 FR	3710
25 FR	3155
30 FR	2970
40 FR	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 9:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..