

RIB F3 - Especificaciones técnicas



Description

RIB F3 es un neumático que se utiliza principalmente en el campo con tractores 2WD/2RM en los trabajos del campo y las operaciones de transporte. Algunas medidas son idóneas para las aplicaciones de transporte realizadas con remolques. RIB F3 es el neumático ideal para todas las operaciones que requieran un elevado nivel de manipulación y maniobras. Ha sido proyectado con una mezcla dura que asegura durabilidad así como una excelente resistencia a los rastrojos.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricultura: Tractor 2WD • Remolque

Version	HD
Type	TT
Tyre Size	9.00 - 16
LI/SS	120 A6/ 112 A8

Dimensions US Standard

Usa code	94042227
Ply Rating	12
Section Width (inch)	9.6
Overall Diameter (inch)	34.6
Static Loaded Radius (inch)	15.2
Rolling Circumference (inch)	101.3
Rim Rec	W 8
Rim Alt	6.00 F ; W 7 ; W 8 L
ECE	E11-106R-004658
TRA Code	F3

Load capacity (lbs)

mph / psi	68
20	3090
25	2470

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 4:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..