

# RIB IMPLEMENT (A) - Especificaciones técnicas



## Description

RIB IMPLEMENT (A) ha sido proyectado para utilizarlo con remolques y maquinaria agrícola en las aplicaciones de transporte y trabajos en el campo. El neumático es ideal para las empresas agrícolas modernas y ofrece excelentes prestaciones tanto por carretera como fuera de carretera. RIB IMPLEMENT (A) es la elección perfecta para todas las condiciones operativas que requieran un elevado nivel de manipulación y de maniobras, así como una reducida compactación del terreno para respetar los cultivos.

## UM

US Standard

## Construction

 BIAS

## Machinery

Agricultura: Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	10.0/80 - 12
LI/SS FREE ROLLING	110 A8

## Dimensions US Standard

Usa code	94010868
Ply Rating	6
Section Width (inch)	10.4
Overall Diameter (inch)	29.4
Static Loaded Radius (inch)	13
Rolling Circumference (inch)	86.1
Rim Rec	9.00
Rim Alt	7.0
ECE	E11-106R-003533

## Load capacity (lbs)

mph / psi	33
5 FR	3270
15 FR	2780
20 FR	2610
25 FR	2340

Printed on 02/07/2024 18:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..