

RIB MASTER - Especificaciones técnicas



Description

RIB MASTER es idóneo para las operaciones de transporte y las operaciones de recogida de heno con remolques, empacadoras de heno y maquinaria agrícola. Este neumático asegura una capacidad elevada de carga y un amplio ciclo de vida del producto.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Empacadora de heno • Maquinaria agrícola • Remolque

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 215/75 - 17.5 |
| LI/SS FREE ROLLING | 142 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94010905 |
| Ply Rating | 16 |
| Section Width (inch) | 8.7 |
| Overall Diameter (inch) | 30.5 |
| Static Loaded Radius (inch) | 14.2 |
| Rolling Circumference (inch) | 90.9 |
| Rim Rec | 6.75 |
| ECE | E11-106R-004593 |

Load capacity (lbs)

| mph / psi | 131 |
|-----------|------|
| 5 FR | 8130 |
| 15 FR | 6960 |
| 20 FR | 6550 |
| 25 FR | 5840 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 0:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..