

RIDEMAX FL 615 - Ficha técnica



Description

RIDEMAX FL 615 es un neumático de flotación radial ideal para ejes no motrices de remolques, camiones cisterna y esparcidores. La estructura con cinturones de acero ofrece una alta resistencia a las perforaciones con mayor durabilidad y alta capacidad de carga. RIDEMAX FL 615 proporciona una baja resistencia al rodamiento en carretera con excelentes propiedades de autolimpieza en el campo. Su hombro redondeado y la amplia área de huella garantizan una óptima protección del suelo.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
800/65 R 32	STEEL BELTED	185 D	185 D	185 D	DW 27 B		830	1853	834	5624	875	TL	E11-106R-007528

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..