

RIDEMAX FL 693 M - Especificaciones técnicas



Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Camión cisterna • Remolque

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 400/45 R 17.5 |
| LI/SS | 139 D |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 400 |
| Overall Diameter (mm) | 800 |
| Static Loaded Radius (mm) | 343 |
| Rolling Circumference (mm) | 2357 |
| SRI (mm) | 390 |
| Rim Rec | 14.00 |
| ECE | E11-106R-006619 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 5.0 | 6.0 |
|------------|------|------|------|------|------|------|------|------|------|------|------|
| 70 | 555 | 710 | 890 | 1000 | 1155 | 1310 | 1440 | 1575 | 1730 | 1950 | 2215 |
| 65 | 610 | 780 | 975 | 1095 | 1265 | 1435 | 1580 | 1730 | 1900 | 2140 | 2430 |
| 50 | 740 | 945 | 1180 | 1330 | 1535 | 1740 | 1915 | 2095 | 2300 | 2595 | 2945 |
| 40 | 830 | 1060 | 1325 | 1490 | 1720 | 1950 | 2150 | 2350 | 2580 | 2910 | 3305 |
| 30 | 920 | 1175 | 1470 | 1655 | 1910 | 2170 | 2390 | 2610 | 2865 | 3230 | 3670 |
| 25 | 960 | 1230 | 1540 | 1730 | 2000 | 2270 | 2500 | 2730 | 3000 | 3380 | 3840 |
| 10 | 1095 | 1400 | 1750 | 1970 | 2275 | 2585 | 2845 | 3110 | 3415 | 3850 | 4375 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 21:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..