

RIDEMAX FL 693 M - Especificaciones técnicas



Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	560/55 R 22.5
LI/SS	162 D

Dimensions US Standard

Usa code	94067626
Section Width (inch)	21.4
Overall Diameter (inch)	46.5
Static Loaded Radius (inch)	21
Rolling Circumference (inch)	142.3
Rim Rec	AG 16.00
Rim Alt	17.00 ; 20.00
ECE	E11-106R-006972

Load capacity (lbs)

mph / psi	17	23	29	35	41	46	52	58	65	73
45	3630	4390	4860	5630	6390	7050	7730	8490	9060	9530
40	3980	4820	5350	6180	7020	7750	8490	9330	9950	10470
30	4820	5830	6470	7480	8500	9380	10270	11290	12050	12670
25	5410	6560	7260	8410	9550	10550	11540	12680	13540	14240
15	6290	7620	8440	9770	11090	12250	13400	14730	15720	16540
5	7160	8670	9620	11120	12630	13950	12580	16780	17910	18850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 21:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..