

RIDEMAX FL 693 M - Especificaciones técnicas



Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

UM

US Standard

Construction

RADIAL

Machinery

Agricultura: Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	600/60 R 30.5
LI/SS	173 D

Dimensions US Standard

Usa code	94069330
Section Width (inch)	23.8
Overall Diameter (inch)	58.9
Static Loaded Radius (inch)	26.8
Rolling Circumference (inch)	177
Rim Rec	AG 20.00
Rim Alt	AG 18.00
ECE	E11-106R-007198

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58	65	73
45	4510	4960	6010	6660	7690	8740	9660	10570	11610	12390	13040
40	4950	5450	6590	7310	8450	9600	10600	11610	12750	13610	14330
30	5990	6590	7980	8850	10240	11620	12840	14050	15430	16480	17340
25	6720	7410	8970	9940	11510	13060	14430	15800	17350	18520	19490
20	7470	8220	9950	11040	12780	14510	16020	17540	19270	20560	21640
15	7810	8610	10420	11550	13360	15180	16750	18340	20160	21520	22640
5	8910	9810	11870	13160	15220	17280	19090	20900	22960	24500	25790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 20:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..