

## RIDEMAX IT 696 - Especificaciones técnicas



### Description

RIDEMAX IT 696 se caracteriza por un único dibujo de la banda de rodadura y una huella amplia que proporcionan un excelente agarre en la carretera, incluso en condiciones invernales. El neumático se presta especialmente para las actividades de los medios municipales y de mantenimiento, gracias a las óptimas características de velocidad y la carcasa robusta. El dibujo de la banda de rodadura ha sido desarrollado especialmente para los trabajos más pesados y garantiza una baja resistencia al rodamiento que se traduce en ahorro de carburante y excelente estabilidad.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	540/80 R 42 IND
LI/SS	168 D/173 A8

## Dimensions US Standard

Usa code	94062409
Section Width (inch)	22
Overall Diameter (inch)	76
Static Loaded Radius (inch)	34.6
Rolling Circumference (inch)	231.3
Rim Rec	W 18 L
Rim Alt	W 16 L
ECE	E11-106R-005714

## Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	5800	7160	8400	9750	10990	12350
30	6270	7740	9070	10540	11870	13340
25	6730	8310	9740	11320	12750	14330
20	8080	9980	11690	13580	15300	17200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 21:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..