

RIDEMAX IT 697 (M+S) - Especificaciones técnicas



Description

RIDEMAX IT 697 M+S es la respuesta perfecta a las exigencias de los subcontratistas modernos en el sector de la agricultura para las operaciones realizadas durante el periodo invernal – perfecto para aplicaciones de transporte y municipales. Este neumático invernal para tractores, garantiza un agarre perfecto en todas las operaciones que se realizan en terrenos con hielo y nieve, sin ninguna necesidad de cadenas de nieve. Gracias a las ranuras de la banda de rodadura y a su carcasa robusta, el tractor se conduce con gran estabilidad, incluso a altas velocidades. El dibujo de la banda de rodadura ha sido proyectado para los trabajos más pesados y asegura una baja resistencia al rodamiento que se traduce en ahorro de carburante y excelente estabilidad.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	540/65 R 30 IND
LI/SS	156 D/161 A8

Dimensions US Standard

Usa code	94048106
Section Width (inch)	20.9
Overall Diameter (inch)	57.6
Static Loaded Radius (inch)	26.5
Rolling Circumference (inch)	175
Rim Rec	W 16 L
Rim Alt	W 18
ECE	E11-106R-003015

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	4140	5110	6000	6970	7850	8820
30	4480	5520	6480	7530	8480	9520
25	4790	5920	6930	8060	9070	10200
20	4970	6140	7200	8360	9410	10580

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 16:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..