

## RIDEMAX IT 697 (M+S) - Especificaciones técnicas



### Description

RIDEMAX IT 697 M+S es la respuesta perfecta a las exigencias de los subcontratistas modernos en el sector de la agricultura para las operaciones realizadas durante el periodo invernal – perfecto para aplicaciones de transporte y municipales. Este neumático invernal para tractores, garantiza un agarre perfecto en todas las operaciones que se realizan en terrenos con hielo y nieve, sin ninguna necesidad de cadenas de nieve. Gracias a las ranuras de la banda de rodadura y a su carcasa robusta, el tractor se conduce con gran estabilidad, incluso a altas velocidades. El dibujo de la banda de rodadura ha sido proyectado para los trabajos más pesados y asegura una baja resistencia al rodamiento que se traduce en ahorro de carburante y excelente estabilidad.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	600/65 R 28 IND
LI/SS	165 A8/160 D

## Dimensions US Standard

Usa code	94066995
Section Width (inch)	23.3
Overall Diameter (inch)	58.7
Static Loaded Radius (inch)	26.9
Rolling Circumference (inch)	177.5
Rim Rec	W 18 L
Rim Alt	DW 20 B
ECE	E11-106R-006760

## Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	4860	5950	6550	7840	8830	9920
30	5260	6440	7080	8470	9550	10710
25	5570	6810	7500	8970	10110	11350
20	5840	7140	7860	9410	10600	11900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 17:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..