

RIDEMAX IT 697 (M+S) - Especificaciones técnicas



Description

RIDEMAX IT 697 M+S es la respuesta perfecta a las exigencias de los subcontratistas modernos en el sector de la agricultura para las operaciones realizadas durante el periodo invernal – perfecto para aplicaciones de transporte y municipales. Este neumático invernal para tractores, garantiza un agarre perfecto en todas las operaciones que se realizan en terrenos con hielo y nieve, sin ninguna necesidad de cadenas de nieve. Gracias a las ranuras de la banda de rodadura y a su carcasa robusta, el tractor se conduce con gran estabilidad, incluso a altas velocidades. El dibujo de la banda de rodadura ha sido proyectado para los trabajos más pesados y asegura una baja resistencia al rodamiento que se traduce en ahorro de carburante y excelente estabilidad.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	710/70 R 42 IND
LI/SS	180 D/185 A8

Dimensions International Standard

TKPH	1
Section Width (mm)	716
Overall Diameter (mm)	2068
Static Loaded Radius (mm)	926
Rolling Circumference (mm)	6264
SRI (mm)	975
Rim Rec	DW23 B
ECE	'E11-106R-005178

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	3760	4640	5440	6320	7120	8000
50	4060	5010	5875	6825	7690	8640
40	4350	5365	6290	7310	8235	9250
30	4510	5570	6530	7585	8545	9600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 17:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..