

RIDEMAX IT 697 (M+S) - Especificaciones técnicas



Description

RIDEMAX IT 697 M+S es la respuesta perfecta a las exigencias de los subcontratistas modernos en el sector de la agricultura para las operaciones realizadas durante el periodo invernal – perfecto para aplicaciones de transporte y municipales. Este neumático invernal para tractores, garantiza un agarre perfecto en todas las operaciones que se realizan en terrenos con hielo y nieve, sin ninguna necesidad de cadenas de nieve. Gracias a las ranuras de la banda de rodadura y a su carcasa robusta, el tractor se conduce con gran estabilidad, incluso a altas velocidades. El dibujo de la banda de rodadura ha sido proyectado para los trabajos más pesados y asegura una baja resistencia al rodamiento que se traduce en ahorro de carburante y excelente estabilidad.

UM

US Standard

Construction

RADIAL

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	710/70 R 42 IND
LI/SS	180 D/185 A8

Dimensions US Standard

Usa code	94058099
TMPH	1
Section Width (inch)	28.2
Overall Diameter (inch)	81.4
Static Loaded Radius (inch)	36.5
Rolling Circumference (inch)	246.6
Rim Rec	DW23 B
ECE	'E11-106R-005178

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	8290	10230	11990	13930	15700	17640
30	8950	11040	12950	15050	16950	19050
25	9590	11830	13870	16110	18150	20390
20	9940	12280	14400	16720	18840	21160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 17:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..