

ROCK GRIP L4 - Especificaciones técnicas



Description

ROCK GRIP (L-4) es un neumático de telas cruzadas para las palas cargadoras de ruedas que se utilizan en las operaciones de carga en terrenos difíciles. La especial mezcla de la banda de rodadura es particularmente resistente a cualquier tipo de corte, reduciendo el riesgo de perforación y consecuentemente el tiempo de parada del vehículo. La profundidad (L-4) de la banda de rodadura garantiza un ciclo de vida prolongado del neumático.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Buldócer • Pala cargadora

Version	STANDARD
Type	TL
Tyre Size	14.00 - 25

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	375
Overall Diameter (mm)	1410
Static Loaded Radius (mm)	649
Rolling Circumference (mm)	4173
Rim Rec	10.00/1.5
TRA Code	L4

Load capacity (Kg)

km/h / bar	10.00
10	10500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 2:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..