

## ROCK GRIP (T) - Especificaciones técnicas



### Description

ROCK GRIP (E-4) es ideal para utilizarlos en camiones volquetes en canteras y para realizar transportes cortos en las minas, llevando cargas pesadas. La especial mezcla de la banda de rodadura reduce al mínimo los cortes y las perforaciones incluso en los terrenos más difíciles. ROCK GRIP (E-4) ofrece una excelente tracción, así como un largo ciclo de vida.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Volquete • Dúmper rígido

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

## Dimensions International Standard

<b>Ply Rating</b>	18
<b>Overall Width (mm)</b>	315
<b>Overall Diameter (mm)</b>	1265
<b>Static Loaded Radius (mm)</b>	595
<b>Rolling Circumference (mm)</b>	3755
<b>Rim Rec</b>	8.5
<b>Rim Alt</b>	8.0

## Load capacity (Kg)

<b>km/h / bar</b>	<b>7.60</b>
<b>80 LS/LD</b>	<b>3750</b>

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 0:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..