

## ROCK GRIP (T) - Ficha técnica



### Description

ROCK GRIP (E-4) es ideal para utilizarlos en camiones volquetes en canteras y para realizar transportes cortos en las minas, llevando cargas pesadas. La especial mezcla de la banda de rodadura reduce al mínimo los cortes y las perforaciones incluso en los terrenos más difíciles. ROCK GRIP (E-4) ofrece una excelente tracción, así como un largo ciclo de vida.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Volquete • Dúmper rígido

SIZE	Version	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
10.00 - 20	STANDARD	18	7.5	7.0	280	1090	0	0	TT
11.00 - 20	STANDARD	18	8.0	7.5	300	1135	0	0	TT
12.00 - 20	STANDARD	20	8.5	8.0	315	1172	0	0	TT
12.00 - 24	STANDARD	18	8.5	8.0	315	1265	595	3755	TT
12.00 - 24	STANDARD	20	8.5	8.0	315	1265	595	3755	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 0:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..