

ROCK STAR IND4 - Especificaciones técnicas



Description

ROCK STAR PORT IND-4 tiene un diseño específico para manipulación de contenedores vacíos y montacargas. Ofrece excelente tracción, y la composición especial de la banda de rodamiento hace que sea mucho menos propenso a rasgarse o astillarse. ROCK STAR PORT IND-4 garantiza unas prestaciones de capacidad de carga y durabilidad excepcionales.

UM

International Standard

Construction

BIAS

Machinery

Industrial: Manipulador de contenedores vacíos • Carretilla elevadora

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	390
Overall Diameter (mm)	1425
Static Loaded Radius (mm)	635
Rolling Circumference (mm)	4350
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	14175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 3:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..