

SKID POWER HD (A) - Ficha técnica

Description

SKID POWER HD ha sido proyectado para las minicargadoras (**skid steer**) que se utilizan en el sector de la construcción. Este neumático se caracteriza para la banda de rodadura extra profunda y la protección de los flancos, asegurando una excelente resistencia a los cortes y los desgarres, así como una extraordinaria duración. SKID POWER HD (A) es el neumático ideal para las superficies terrosas y los trabajos más pesados.



UM

US Standard

Construction

 BIAS

Machinery

Industrial: Minicargadora compacta

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 8.5 - 8	STANDARD	94030422	97 A2	8	7.00 I - 55 ; I - 70 ; I - 90		8.3	18.1	8.1	53.4	TL	E11-106R-005559
23 X 8.5 - 12	IMPLEMENT	94056095	87 A8	6	7.00 I - 55	7.00 I - 70 ; 7 JA	8.5	23	10.7	69.4	TL	E11-106R-003361
23 X 8.50 - 12	IMPLEMENT	94056101	98 A8	12	7.00 I - 55	7.00 I - 70 ; 7 JA	8.5	23	10.7	69.4	TL	E11-106R-003537
23 X 8.50 - 12	STANDARD	94017812		12	7.00 I - 55	7.00 I - 70 ; 7 JA	8.5	23	10.7	69.4	TL	E11-106R-003569
23 X 8.50 - 12	STANDARD	94017775		6	7.00 I - 55	7.00 I - 70 ; 7 JA	8.5	23	10.7	69.4	TL	
23 X 8.50 - 12	STANDARD	94017805		8	7.00 I - 55	7.00 I - 70 ; 7 JA	8.5	23	10.7	69.4	TL	
26 X 12 - 12	IMPLEMENT	94056019	114 A8	12	10.50 I - 55	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA	12	26	11.7	76.7	TL	E11-106R-003538
26 X 12 - 12	STANDARD	94017850		12	10.50 I - 55	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA	12	26	12.1	78.3	TL	
26 X 12 - 12	STANDARD	94017836		8	10.50 I - 55	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA	12	26	11.7	76.7	TL	E11-106R-004118
26 X 12 - 12	STANDARD	94017843		10	10.50 I - 55	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA	12	26	11.7	76.7	TL	
27 X 10 - 12 (250/75 - 12)	INDUSTRIAL	94026203	152 A2	14	8.00 G		10	27.6	0	0	TT	E11-106R-006176
27 X 10.5 - 15	IMPLEMENT	94056026	105 A8	8	8 LB		10.1	26.9	12.8	80.2	TL	E11-106R-003539
27 X 10.5 - 15	STANDARD	94017867		8	8 LB		10.1	26.9	12.8	80.2	TL	E11-106R-007197
27 X 10.5 - 15	TRACTOR TRAILER	94057528	105 A8	8	8 LB		10.1	26.9	12.8	80.2	TL	E11-106R-003376
27 X 8.5 - 15	IMPLEMENT	94056033	102 A8	8	7 JA		8.6	26.6	12.8	78.9	TL	E11-106R-003540
27 X 8.50 - 15	STANDARD	94017881		8	7 JA		8.6	26.6	12.8	78.9	TL	
31 X 15.5 - 15	IMPLEMENT	94056057	125 A8	10	13 LB		15.7	31.1	14.9	94.9	TL	E11-106R-003375
31 X 15.5 - 15	STANDARD	94017911		8	13 LB		15.7	31.1	14.9	94.9	TL	
31 X 15.5 - 15	STANDARD	94065226	139 A2/121 B	10	13 LB		15.7	31.1	14.9	94.9	TL	E11-106R-003571
10 - 16.5	IMPLEMENT	94055685	116 A8	8	8.25		10.5	30.7	14.3	92.5	TL	E11-106R-003665
10 - 16.5	STANDARD	94017645		10	8.25		10.5	30.7	14.3	92.5	TL	E11-106R-005556
10 - 16.5	STANDARD	94017614		8	8.25		10.5	30.7	14.3	92.5	TL	
12 - 16.5	IMPLEMENT	94055739	130 A8	12	9.75		12.8	33.5	15.3	101.2	TL	E11-106R-003568
12 - 16.5	IMPLEMENT	94055692	125 A8	10	9.75		12.8	33.5	15.3	101.2	TL	E11-106R-003541

12 - 16.5	STANDARD	94069484		14	9.75		12.8	33.5	15.3	101.2	TL	
12 - 16.5	STANDARD	94017706		12	9.75		12.8	33.5	15.3	101.2	TL	
12 - 16.5	STANDARD	94017676		10	9.75		12.8	33.5	15.3	101.2	TL	
260/70 - 16.5 (10 - 16.5)	IMPLEMENT	94052219	120 A8	10	8.25		10.5	30.5	14	90.4	TL	E4-106R-002338
31.5 X 13 - 16.5	IMPLEMENT	94056064	124 A8	10	9.75		13	31.3	14.3	92.3	TL	E11-106R-003542
31.5 X 13 - 16.5	STANDARD	94017904		10	9.75		13	31.3	14.3	92.3	TL	
33 X 15.5 - 16.5	IMPLEMENT	94057245	131 A8	12	13.00		15.5	33	15.2	100.9	TL	E11-106R-003018
33 X 15.5 - 16.5	STANDARD	94060825	151 A2	14	13.00		15.5	33	15.2	100.9	TL	E11-106R-006606
33 X 15.5 - 16.5	STANDARD	94017942	148 A2	12	13.00		15.5	33	15.2	100.9	TL	E11-106R-003505
14 - 17.5	IMPLEMENT	94056071	140 A8	14	10.50		13.8	36.6	16.5	108	TL	
14 - 17.5	STANDARD	94017720		14	10.50		13.8	36.6	16.5	108	TL	
15 - 19.5	IMPLEMENT	94056088	146 A8	14	11.75	12.25	15.7	40.1	18.2	121.1	TL	E11-106R-003656
15 - 19.5	STANDARD	94017744		14	11.75	12.25	15.7	40.1	18.2	121.1	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..