

## SL 441 - Especificaciones técnicas



### Description

SL 441 es un neumático desarrollado para los trabajos del campo y operaciones de transporte con remolques y maquinaria agrícola. SL 441 ha sido proyectado para ofrecer una excelente capacidad de carga y un amplio ciclo de vida del producto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Maquinaria agrícola • Remolque

Version	STANDARD
Type	TT
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	106 A8

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	210
Overall Diameter (mm)	610
Static Loaded Radius (mm)	278
Rolling Circumference (mm)	1785
Rim Rec	AG 6.75

## Load capacity (Kg)

km/h / bar	5.00
10 FR	1330
25 FR	1130
30 FR	1065
40 FR	950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 13:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..