

## SM 55 L5S - Especificaciones técnicas



### Description

SM 55 (L-5S) es un neumático de telas cruzadas ideal para utilizarlo en las minas subterráneas. La banda de rodadura está realizada con una mezcla especial, resistente a los cortes y los desgarres, caracterizada por una profundidad extra L-5S. Esto se traduce en reducidos tiempos de parada de la máquina que garantizan una vida prolongada del neumático. Este neumático también está disponible en la versión "steel belted" con cinturones de acero.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Volquete de perfil bajo • Vehículos para minería subterránea

Version	STANDARD
Type	TL
Tyre Size	17.5 - 25

## Dimensions International Standard

<b>Ply Rating</b>	20
<b>Overall Width (mm)</b>	438
<b>Overall Diameter (mm)</b>	1375
<b>Static Loaded Radius (mm)</b>	631
<b>Rolling Circumference (mm)</b>	4043
<b>Rim Rec</b>	14.00/1.5
<b>Rim Alt</b>	14.00/1.3 ; 14.00/1.4 (DC)
<b>TRA Code</b>	L5S

## Load capacity (Kg)

	km/h / bar	5.75
	10	8250
	15	7180
	25	6600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 13:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..