

SNOW - EXCEL - Ficha técnica



Description

SNOW-EXCEL es específicamente idóneo para las aplicaciones industriales y de construcción que se realizan en la carretera en condiciones invernales. Este neumático se caracteriza para su excelente tracción y es ideal para los trabajos realizados en la nieve y el hielo. El dibujo especial de la banda de rodadura elimina el riesgo de derrape.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Tractor

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type
16.9 - 24	STANDARD		10	DW 15 L	DW 14 L	445	1320	607	3978		
16.9 - 24	STANDARD	149 A8	12	DW 15 L	DW 14 L	445	1320	607	3978	625	TL
17.5 - 25	STANDARD		12	14.00/1.5		445	1370	612	4070		TL
20.5 - 25	STANDARD		16	17.00/2.0		524	1490	657	4434		TL
23.5 - 25	STANDARD		16	19.50/2.5		600	1620	692	4787		TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..