

## SNOW - RIDE (B) - Especificaciones técnicas



### Description

SNOW-RIDE es específicamente idóneo para las operaciones que se realizan en la carretera en condiciones invernales con palas cargadoras y excavadoras. Este neumático se caracteriza para una excelente tracción y es ideal para los trabajos realizados en la nieve y el hielo. El dibujo especial de la banda de rodadura elimina los riesgos de derrape.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Buldócer • Pala cargadora

Version	STANDARD
Type	TL
Tyre Size	17.5 - 25

## Dimensions US Standard

Usa code	94043446
Ply Rating	12
Section Width (inch)	17.5
Overall Diameter (inch)	53.1
Static Loaded Radius (inch)	23.9
Rolling Circumference (inch)	159.2
Rim Rec	14.00/1.5
TRA Code	L2

## Load capacity (lbs)

mph / psi	51
5	13600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..