

SR 713 - Especificaciones técnicas



Description

SR 713 es un neumático radial **All Steel** con tecnología VF para maquinaria agrícola. Este neumático se caracteriza por una robusta carcasa con cinturones de acero multicapa y por una banda de rodadura con un dibujo de ranuras múltiples que garantizan una baja resistencia al rodamiento, además del desgaste uniforme de la banda de rodadura. Gracias a una huella más ancha, este neumático VF asegura una reducida compactación del suelo. SR 713 se distingue tanto en términos de prestaciones como por su fiabilidad, ofreciendo óptimos niveles de velocidad incluso por carretera.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Maquinaria agrícola

Version	STANDARD
Type	TL
Tyre Size	VF 295/75 R 22.5
LI/SS	155 D

Dimensions US Standard

Usa code	94068920
Overall Width (inch)	11
Overall Diameter (inch)	40.2
Static Loaded Radius (inch)	17.7
Rolling Circumference (inch)	119.8
Rim Rec	9.00
Rim Alt	8.25
ECE	E11-106R-006977
TRA Code	I1

Load capacity (lbs)

mph/psi	35	38	41	44	46	49	52	55	58	61	64	67	70
0	10765	11360	12330	13065	13430	13800	14720	15180	15985	17020	17480	18515	19665
5	8425	8890	9650	10225	10510	10800	11520	11880	12510	13320	13680	14490	15390
10	8095	8545	9275	9825	10105	10380	11070	11420	12025	12800	13150	13925	14790
15	7395	7805	8470	8975	9225	9480	10110	10430	10980	11690	12010	12720	13510
20	7065	7460	8095	8575	8820	9060	9665	9965	10495	11175	11475	12155	12910
25	6365	6720	7290	7725	7940	8160	8705	8975	9450	10065	10335	10950	11630
30	5665	5975	6485	6875	7065	7260	7745	7985	8410	8955	9195	9740	10345
35	5010	5285	5735	6080	6250	6420	6850	7060	7435	7920	8130	8615	9150
40	4680	4940	5360	5680	5840	6000	6400	6600	6950	7400	7600	8050	8550
43	4260	4495	4880	5170	5315	5460	5825	6005	6325	6735	6915	7325	7780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 14:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..