

SUPER GRADER - Especificaciones técnicas



Description

SUPER GRADER (G-2) es un neumático diagonal específicamente desarrollado para las motoniveladoras. Presenta una excelente tracción y óptimas propiedades de auto limpieza. SUPER GRADER ha sido realizado con una mezcla especial que permite un ciclo de vida prolongado del neumático y se puede utilizar en los trabajos más pesados.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Motoniveladora

Version	STANDARD
Type	TL
Tyre Size	16.00 - 24

Dimensions International Standard

Ply Rating	16
Overall Width (mm)	430
Overall Diameter (mm)	1450
Static Loaded Radius (mm)	644
Rolling Circumference (mm)	4307
Rim Rec	10.00 VA SDC
TRA Code	G2

Load capacity (Kg)

km/h / bar	3.00
40	4500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 18:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..