

TF 8181 - Ficha técnica



Description

TF 8181 es un neumático que se utiliza tanto en el campo como en la carretera para los tractores 2WD/2RM empleados en los trabajos del campo y de transporte. Este neumático asegura un excelente comportamiento de la dirección.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Tractor 2WD

Industrial: Remolque

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
4.00 - 15	STANDARD	94056804	F2	62 A8	4	3.00 D	4 J	4.4	23.8	11.3	72.2	TT	E11-106R-005191
5.00 - 15	SPECIAL	94043903	F2	76 A8	6	4.00 E	3.00 D ; 4 J ; 4½ J	5.6	25.8	12.1	76.8	TT	E11-106R-005213
5.00 - 15	STANDARD	94020539	F2	69 A8	4	4.00 E	3.00 D ; 4 J ; 4½ J	5.6	25.8	12.1	76.8	TT	
5.00 - 15	STANDARD	94020546	F2	76 A8	6	4.00 E	3.00 D ; 4 J ; 4½ J	5.6	25.8	12.1	76.8	TT	E4-106R-001951
10.00 - 16	STANDARD	94032754	F2	110 A8	8	W 8	W 8 L	10.7	35.2	16.2	105	TT	E4-106R-002672
11.00 - 16	STANDARD	94032761	F2	114 A8	8	W 10 L	W 8 ; W 8 L	12.8	38.2	17.6	115	TT	E4-106R-002673
4.00 - 16	STANDARD	94036400	F2	61 A8	4	3.00 D		4.4	24.8	11.9	73.9	TT	E4-106R-002183
4.50 - 16	STANDARD	94020522	F2	65 A8	4	3.00 D		4.8	25.8	12.2	76.9	TT	E4-106R-001953
5.00 - 16	SPECIAL	94027774	F2	76 A8	6	4.00 E	3.00 D ; 4 J ; 4½ J	5.5	26.8	12.7	79.7	TT	E11-106R-004090
5.00 - 16	STANDARD	94020553	F2	69 A8	4	4.00 E	3.00 D ; 4 J ; 4½ J	5.5	26.8	12.7	79.7	TT	
5.00 - 16	STANDARD	94020560	F2	76 A8	6	4.00 E	3.00 D ; 4 J ; 4½ J	5.5	26.8	12.7	79.7	TT	E4-106R-001954
5.50 - 16	SPECIAL	94034697	F2	82 A8	6	4.00 E	3.50 D ; 4.50 E	6.2	28.3	13.4	84.4	TT	
5.50 - 16	STANDARD	94020577	F2	82 A8	6	4.00 E	3.50 D ; 4.50 E	6.2	28.3	13.4	84.4	TT	E4-106R-001955
6.00 - 16	SPECIAL	94026432	F2	85 A8	6	4.50 E	4.00 E ; 5 K ; 5.00 F	6.8	29.3	13.8	87.4	TT	E11-106R-004410
6.00 - 16	SPECIAL	94030262	F2	91 A8	8	4.50 E	4.00 E ; 5 K ; 5.00 F	6.8	29.3	13.8	87.4	TT	E11-106R-004415
6.00 - 16	STANDARD	94020584	F2	85 A8	6	4.50 E	4.00 E ; 5 K ; 5.00 F	6.8	29.3	13.8	87.4	TT	E4-106R-001959
6.00 - 16	STANDARD	94020591	F2	91 A8	8	4.50 E	4.00 E ; 5 K ; 5.00 F	6.8	29.3	13.8	87.4	TT	E4-106R-002186
6.50 - 16	HD	94029389	F2	90 A8	8	4.50 E	4.00 E ; 5 K ; 5.00 F ; 5.50 F	7.1	30.3	14.2	90.4	TT	E11-106R-005227
6.50 - 16	SPECIAL	94031511	F2	94 A8	10	4.50 E	4.00 E ; 5 K ; 5.00 F ; 5.50 F	7.1	30.3	14.2	90.4	TT	E4-106R-002707
6.50 - 16	SPECIAL	94045464	F2	88 A8	6	4.50 E	4.00 E ; 5 K ; 5.00 F ; 5.50 F	7.1	30.3	14.2	90.4	TT	
6.50 - 16	STANDARD	94020614	F2	88 A8	6	4.50 E	4.00 E ; 5 K ; 5.00 F ; 5.50 F	7.1	30.3	14.2	90.4	TT	E4-106R-001960
7.50 - 16	IMPLEMENT	94030521	F2	122 A6	14	5.50 F	5.00 F ; 5 K ; 6.00 F	8.1	32.3	15.1	96.3	TT	E4-106R-002670
7.50 - 16	SPECIAL	94026487	F2	94 A8	6	5.50 F	5.00 F ; 5 K ; 6.00 F	8.1	32.3	15.1	96.3	TT	E11-106R-004412
7.50 - 16	SPECIAL	94026494	F2	99 A8	8	5.50 F	5.00 F ; 5 K ; 6.00 F	8.1	32.3	15.1	96.3	TT	E11-106R-004413
7.50 - 16	STANDARD	94020645	F2	94 A8	6	5.50 F	5.00 F ; 5 K ; 6.00 F	8.1	32.3	15.1	96.3	TT	E4-106R-002634
7.50 - 16	STANDARD	94020652	F2	99 A8	8	5.50 F	5.00 F ; 5 K ; 6.00 F	8.1	32.3	15.1	96.3	TT	E4-106R-002709
7.50 - 16	STANDARD	94031375	F2	101 A8	10	5.50 F	5.00 F ; 5 K ; 6.00 F	8.1	32.3	15.1	96.3	TT	E4-106R-002708
6.00 - 18	STANDARD	94055807	F2	94 A8	8	4.50 E	4.00 E ; 5.00 F	6.8	31.5	14.7	94.9	TT	E11-106R-005253
7.50 - 18	HD	94057139	F2	102 A8	8	5.50 F		8.2	34.4	16.1	102.6	TT	E11-106R-005254
7.50 - 18	SPECIAL	94057122	F2	97 A8	6	5.50 F		8.2	34.4	16.1	102.6	TT	
7.50 - 18	SPECIAL	94045457	F2	102	8	5.50 F		8.2	34.4	16.1	102.6	TT	E11-106R-

A8											005254		
7.50 - 18	STANDARD	94020669	F2	97 A8	6	5.50 F		8.2	34.4	16.1	102.6	TT	E4-106R-002639
7.50 - 18	STANDARD	94020676	F2	102 A8	8	5.50 F		8.2	34.4	16.1	102.6	TT	E4-106R-002645
6.00 - 19	STANDARD	94020607	F2	89 A8	6	4.50 E	4.00 E ; 5.00 F	6.9	32.7	15.2	95.5	TT	E4-106R-001963
6.50 - 20	SPECIAL	94032266	F2	97 A8	8	5.00 F	4.00 E ; 5.50 F	7.1	34.1	16.1	101.5	TT	
6.50 - 20	STANDARD	94020638	F2	93 A8	6	5.00 F	4.00 E ; 5.50 F	7.1	34.1	16.1	101.5	TT	E4-106R-001964
6.50 - 20	STANDARD	94027705	F2	97 A8	8	5.00 F	4.00 E ; 5.50 F	7.1	34.1	16.1	101.5	TT	E4-106R-002833
7.50 - 20	HD	94021369	F2	99 A8	6	5.50 F	5.00 F	8.1	36	17	107.3	TT	
7.50 - 20	HD	94025688	F2	105 A8	8	5.50 F	5.00 F	8.1	36	17	107.3	TT	E11-106R-004314
7.50 - 20	SPECIAL	94045440	F2	105 A8	8	5.50 F	5.00 F	8.1	36	17	107.3	TT	E11-106R-005255
7.50 - 20	STANDARD	94020683	F2	99 A8	6	5.50 F	5.00 F	8.1	36	17	107.3	TT	E4-106R-002635
7.50 - 20	STANDARD	94020690	F2	105 A8	8	5.50 F	5.00 F	8.1	36	17	107.3	TT	E4-106R-002710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..