

## TF 9393 - Ficha técnica



### Description

TF 9393 es un neumático agrícola frontal proyectado específicamente para minitractores en los trabajos del campo y particularmente en suelos sueltos. La banda de rodadura se caracteriza por una amplia parte central y por costillas en el área del hombro. El particular diseño de la banda de rodadura asegura un óptimo giro de dirección en todas las superficies.

### UM

US Standard

### Construction

BIAS

### Machinery

Agricultura: Minitractor

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type
7.50 - 16	STANDARD	94046263	F2	103 A6	8	5.50 F	5.00 F ; 6.00 F	8.3	31.9	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..